

RUL-C features not available with Old RUL

- 3 Lumen/Wattage packages as opposed to one
- Multivolt as opposed to 120v only
- Diming driver standard, Dali driver available
- 6, 10 & 20 KV surge available as opposed to 6 & 10 only
- 7 Pin photo cell receptacle available to accept smart nodes
- Standard 5 year warranty with 10 year as an option
- 2 options on prewired with individual wires coming out of the fixture as opposed to the old way of an SO cord which linemen hate.
- 7 kitting options as opposed to 2 will eliminate have to have a special in many cases.
- More shielding and Refractor options

RUL-C ... “Increased SKUs and Optionality”



Increased Application Reach and Value

	RUL - A	RUL - C
Lumen Packages	5,000	3,000 / 6,000 / 9,000
LPW (Type 5 – 4000K)	114	150 / 143 / 155 (>25% Increase)
CCTs	3000K / 4000K	3000K / 4000K / 5700K
CRI	≥ 70	≥ 70
Voltage	120V	120 – 277V
Controls	None	0-10V (Standard) / DALI Option
Utility Label Standard	Yes	Yes
Receptacle	3-Pin	3-Pin / 7-Pin Option
Surge Suppression	6kV / 10kV Option	6kV / 10kV & 20kV Options
Warranty	10 Years	Choice of 5 Year or 10 Year Warranty
U.S. Assembly	Assembled in Racine, WI	Assembled in Racine, WI
LMF @ 50K / 100K Hours (25 °C)	0.88 (50K Hours) / 0.79 (100K Hours)	0.88 (50K Hours) / 0.79 (100K Hours)
Dark Sky Friendly	No	Yes (3000K w/Cutoff Shield Version)

